

SELF-ADHESIVE BUMPERS

Fastex Bumpers are ideal for providing skid and mar resistance for telephones and other electronic equipment. The installation is fast and secure and involves minimal labor.



In this application, the Fastex Bumper is adhered to a wooden cabinet door. The Bumper provides shock and sound dampening when the hinged door is closed.



PVC Bumpers

- Acrylic-based adhesive for long-term adhesion;
- Adhesive has excellent solvent and ultraviolet resistance;
- High shear strength;
- 5 Standard Colors: White, Black, Gray, Brown, Natural.
(Note: Not all parts available in each color)

SHAPE/DESCRIPTION	STYLE NUMBER	PART NUMBER	SIZE	STANDARD COLORS**
CYLINDRICAL	M-1	5001-01-00	HGT. .140" DIA. .500"	BLACK/GRAY/NATURAL
	M-5	5005-01-00	HGT. .070" DIA. .500"	WHITE/BLACK/NATURAL
	M-6	5006-01-00	HGT. .250" DIA. .500"	BLACK/NATURAL
	M-11	5011-01-00	HGT. .400" DIA. .645"	WHITE/BLACK
	M-25	5025-01-00	HGT. .250" DIA. .830"	BLACK
	M-26	5026-01-00	HGT. .090" DIA. .500"	BLACK/NATURAL
	M-29	5029-01-00	HGT. .325" DIA. .500"	GRAY
	M-31	5031-01-00	HGT. .115" DIA. .500"	BLACK
	M-34	5034-01-00	HGT. .115" DIA. .645"	BLACK
SQUARE	M-3	5003-01-00	HGT. .200" SQ. .500"	BLACK
	M-4	5004-01-00	HGT. .340" SQ. .760"	BLACK
	M-10	5010-01-00	HGT. .260" SQ. .510"	BLACK
	M-22	5022-01-00	HGT. .130" SQ. .645"	BLACK
	M-33	5033-01-00	HGT. .185" SQ. .375"	BLACK
TAPERED SQUARE	M-19	5019-01-00	HGT. .300" SQ. .810"	BLACK
	M-32	5032-01-00	HGT. .120" SQ. .500"	BLACK
HEMISPHERE	M-2	5002-01-00	HGT. .200" DIA. .437"	BLACK
	M-15	5015-01-00	HGT. .320" DIA. .645"	BLACK
CIRCULAR DEPRESSED	M-17	5017-01-00	HGT. .400" DIA. .875"	BLACK
	M-30	5030-01-00 (DOOR STOP)	HGT. .560" DIA. 2.0"	WHITE
CYLINDRICAL CONCAVITY	M-18	5018-01-00	HGT. .140" DIA. .500"	GRAY

*All dimensions ± .02 inches measured without adhesive liner. **Other colors available.
NOTE: Bumper may not be centered on skirt area of die cut. Dimensions listed are nominal.

Special Application Bumpers

Self-adhesive bumpers made from a specially formulated urethane provide a quick and effective method of providing additional support for printed circuit boards. The bumper can withstand 50 lbs. of weight with a deflection of less than .020". UL flammability rating is 94V-2. UL File Number E83785.

SHAPE/DESCRIPTION	STYLE NUMBER	PART NUMBER	SIZE
HARD DUROMETER MATERIAL 85 PLUS SHORE A	Can be molded in any style with a height greater than .110"	5076- Material End Code	Can be molded in any style with a height greater than .110"

